

# BPG08 GRP Enclosure

IP66/67

The BPG enclosure, crafted from robust glass-reinforced polyester (GRP), is designed for durability and versatility. Built for demanding environments, the BPG enclosure offers reliable protection with its resistance to impact and extreme temperatures, along with exceptional ingress protection, making it an ideal solution for industrial applications. The range is available in various sizes to meet diverse needs.

- Ambient temperature range -65°C to +130°
- Fire rated to BS EN 50200
- High impact resistance
- High IP rating
- Highly resistant to hydrocarbons and other industrial compounds



## Enclosure Information

Product Reference	Width (mm)	Height (mm)	Depth (mm)	Weight (kg)
EBPG08	160	160	90	1.060

## Standard Specifications

Enclosure Material	Glass Reinforced Polyester (Grey - RAL7001)				
Ingress Protection	IP66/67 to EN60529				
Impact Resistance	IK08				
Service Temperature	-65°C to +130°C				
Terminal Quantity	WDU 2.5	WDU 4	WDU 6	WDU 10	WDU 16
	19	15	11	8	6
Certification	Type of Protection		Equipment Coding		
	Ex eb (Increased Safety)		Ex eb IIC T_ Gb		
	Ex ta (Dust Ignition)		Ex ta IIIC T_°C Da		
	Ex ia/ib (Intrinsic Safety)		Ex ia IIC T_ Ga, Ex ib IIC T_ Gb		
	Ex tb (Dust Protection)		Ex tb IIC T_°C Db		
Certificate Numbers	ATEX		CML 20ATEX3009X		
	IECEX		IECEX CML 20.0003X		
	UKEX		CML 21UKEX3471X		
	ECAS Ex (UAE)		24-06-23146/Q24-06-049342/NB0007		
	InMetro (Brazil)		NCC 24.0079 X		
	TRCU (Eurasian Customs Union)		RU C-GB.HA65.B.01696/23		

## Options

BPGC		
Material	Carbon Loaded Glass Reinforced Polyester (Black - RAL9005)	
Ingress Protection	IP66/67 to EN60529	
Impact Resistance	IK09	
Service Temperature	-65°C to +130°C	

Please note the BPGC Range is not fire rated.

## Accessories

Earth Continuity Plate: Zintec, Copper, Brass
Breather Drain
Mounting Feet
Component Mounting Plate: Stainless Steel, Zintec, Pertinax
Internal Earthing Bar (subject to available space)
External Hinges
DIN standard mounting rail (TS15, TS32, TS35)
External Earth Stud

## Dimensions

